


CHARACTERISTICS

- IP65 rated waterproof luminaire with high impact resistance IK11+/80 J rated curved aluminium profile
- Opalescent or clear diffuser with louvres or with optics
- Can be suspension mounted using a mounting kit made from shiny, nickel-plated brass, with 3m stainless steel finger line supplied as standard
- Not apparent quick power connection
- Fine texture RAL 7016 anthracite grey ● finish

OPTIONS AVAILABLE ON REQUEST

- Motion detector adjustable via radio-control or smartphone
- Pack emergency version available
- High UV resistance or anti-graffiti coating
- Through wiring
- Side cable entry

Optional mounting support available to order separately:
- Suspension kit: 9854 0002

 Vandal-proof tool available to order separately.
Inset code M4: 9800 0036
+

Inset code M5: 9800 0012



Radio-control for wireless control available to order separately.
Code: 9800 0010

SYSTEO S – Opalescent

220-240 V AC / 50/60 Hz



 direct 772

Length L (mm)	Power rating (W)	Luminaire light output (lm) 4000 K	Luminaire efficacy (lm/W)	Opalescent surface mounted
1066	9	850	97	5608 14--
1066	14	1400	100	5602 14--
1066	26	2700	104	5603 14--
1346	19	1950	103	5604 14--
1346	37	3800	103	5605 14--

Durability: L80B10 / over 72 000 hours
L90B50 / 50 000 hours

Codification for 3000 K
colour temperature:
replace the figure 4 by a 3.

for instance 4000K: 5602 14--
3000K: 5602 13--

Codification: replace the two dashes (--)
by the appropriate figures:
for instance 5602 14--

- 00 NO DETECTION
- 16 WITH PRO DETECTION + RADIO-CONTROL
- 21 DALI DIMMABLE + SWITCH DIMMING
- 44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
- 45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

SYSTEO S – Clear, with louvres

220-240 V AC / 50/60 Hz



direct 772

For ceiling-mounting versions only

Length L (mm)	Power rating (W)	Luminaire light output (lm) 4000 K*	Luminaire efficacy (lm/W)	Clear surface mounted
1066	11	1400	127	5636 14--
1066	16	2000	125	5637 14--
1346	16	2100	131	5638 14--
1346	26	3300	127	5639 14--

Durability: L80B10 / over 72 000 hours
L90B50 / 50 000 hours

* For precise figures, please refer to the technical data sheet.
UGR rating to be confirmed by a lighting study.

Codification for 3000 K colour temperature:
replace the figure 4 by a 3

for instance 4000K: 5636 14--
3000K: 5636 13--

Codification: replace the two dashes (--)
by the appropriate figures:
for instance 5636 14--

00 NO DETECTION
21 DALI DIMMABLE + SWITCH DIMMING

SYSTEO S – Clear, with optics

220-240 V AC / 50/60 Hz



direct 772

For ceiling mounting versions only

Length L (mm)	Power rating (W)	Luminaire light output (lm) 4000 K*	Mounted Clear 40° optics	Mounted Clear 60° optics	Mounted Clear 90° optics	Mounted Clear batwing optics	Mounted Clear wallwasher optics
1066	9	1050	5614 14--	5619 14--	5624 14--	5629 14--	5634 14--
1066	14	1750	5611 14--	5616 14--	5621 14--	5626 14--	5631 14--
1346	16	2450	5612 14--	5617 14--	5622 14--	5627 14--	5632 14--

Durability: L80B10 / over 72 000 hours
L90B50 / 50 000 hours

* For precise figures, please refer to the technical data sheet.
UGR rating to be confirmed by a lighting study.

Codification for 3000 K colour temperature:
replace the figure 4 by a 3.

for instance 4000K: 5631 14--
3000K: 5631 13--

Codification: replace the two dashes (--)
by the appropriate figures:
for instance 5631 14--

00 NO DETECTION
16 WITH PRO DETECTION + RADIO-CONTROL
21 DALI DIMMABLE + SWITCH DIMMING
44 WITH PRO DETECTION + RADIO-CONTROL + EXTINCTION WARNING
45 WITH PRO DETECTION + RADIO-CONTROL + STANDBY WARNING

