



SOFFITE LED

Features

- Input voltage: 220–240 V AC, 50/60 Hz
- Input voltage range: 198–264 V AC
- Electrical protection class 1
- IP: 42
- IK: 10 / 20 joules
- IRC 80
- Incandescent wire test 850 °C / 30
- Rated ambient operating temperature: 25 °C to NF EN 60598-1 standard
- VK22 corner mounted
- SDCM (Standard Deviation Colour Matching): 3
- LED module life > 50,000 hr (L90B50)
- Photobiological hazard: RG0

Applications

- Indoor angle luminaire, vandal-resistant
- Conditions of use:
 - Models with detection: installation indoor only
 - Installation positions: refer to installation instructions

Materials

- Base: body and end caps in white lacquered aluminium
- Diffuser: opal polycarbonate
- RoHS: the products contain no prohibited substances as defined in the European Directive 2011/65/UE and amendments

Colours / Finish

- Finish lacquered white RAL9016

Wiring

- Supply terminal block: automatic, dual-entry, for 4 × 1.5 mm² conductors

Closing

- None (opening secured by special tool)

Facilities available

- In-line fitting (side running wiring): add the suffix **9801** to the product – example: 3015 0300 **9801**

- Open on the right hand side: add the suffix **9803** to the product – example: 3015 0300 **9803**
- Open on the left hand side: add the suffix **9804** to the product – example: 3015 0300 **9804**

Tools *(to be ordered separately)*


- Soffite opening tool - code: **9800 0009**

Approvals

Certificates available:

- CE certificate (as per EN60598-1 / 2-1)
- Incandescent Wire Test certificate (depending on product)
- Eligible for the BAR-EQ-110 energy economy certificate for detection versions
- Eligible for the BAT-EQ-127

Dimensions



*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*

SOFFITE LED							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	12	-	1280	107	615	30150300
Soffite 2 modules LLC900	4000	12	-	1330	111	615	30150400
Soffite 2 modules LLC1300	3000	18	-	2180	121	615	30160300
Soffite 2 modules LLC1300	4000	18	-	2270	126	615	30160400
Soffite 3 modules LLC900	3000	14	-	1610	115	915	30170300
Soffite 3 modules LLC900	4000	14	-	1680	120	915	30170400
Soffite 3 modules LLC1300	3000	26	-	3120	120	915	30180300
Soffite 3 modules LLC1300	4000	26	-	3250	125	915	30180400
Soffite 4 modules LLC900	3000	17	-	2260	133	1195	30190300
Soffite 4 modules LLC900	4000	17	-	2350	138	1195	30190400
Soffite 4 modules LLC1300	3000	33	-	4060	123	1195	30200300
Soffite 4 modules LLC1300	4000	33	-	4240	128	1195	30200400
Soffite 5 modules LLC900	3000	26	-	3210	123	1475	30210300
Soffite 5 modules LLC900	4000	26	-	3340	128	1475	30210400
Soffite 5 modules LLC1300	3000	41	-	5120	125	1475	30220300
Soffite 5 modules LLC1300	4000	41	-	5340	130	1475	30220400
SOFFITE LED with Pro detection (- technical specifications and conditions of use for detection (NOT0410): www.securlite.com (NOT0410)							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	<0,5	1280	98	760	30150312
Soffite 2 modules LLC900	4000	13	<0,5	1330	102	760	30150412
Soffite 2 modules LLC1300	3000	19	<0,5	2180	115	760	30160312
Soffite 2 modules LLC1300	4000	19	<0,5	2270	119	760	30160412
Soffite 3 modules LLC900	3000	15	<0,5	1610	107	1060	30170312
Soffite 3 modules LLC900	4000	15	<0,5	1680	112	1060	30170412
Soffite 3 modules LLC1300	3000	27	<0,5	3120	116	1060	30180312
Soffite 3 modules LLC1300	4000	27	<0,5	3250	120	1060	30180412
Soffite 4 modules LLC900	3000	18	<0,5	2260	126	1340	30190312
Soffite 4 modules LLC900	4000	18	<0,5	2350	131	1340	30190412
Soffite 4 modules LLC1300	3000	34	<0,5	4060	119	1340	30200312
Soffite 4 modules LLC1300	4000	34	<0,5	4240	125	1340	30200412
Soffite 5 modules LLC900	3000	27	<0,5	3210	119	1620	30210312
Soffite 5 modules LLC900	4000	27	<0,5	3340	124	1620	30210412
Soffite 5 modules LLC1300	3000	42	<0,5	5120	122	1620	30220312
Soffite 5 modules LLC1300	4000	42	<0,5	5340	127	1620	30220412
SOFFITE LED with Pro detection + extinction warning (1) - technical specifications and conditions of use for detection www.securlite.com (NOT0410)							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	<0,5	1280	98	760	30150314
Soffite 2 modules LLC900	4000	13	<0,5	1330	102	760	30150414
Soffite 2 modules LLC1300	3000	19	<0,5	2180	115	760	30160314
Soffite 2 modules LLC1300	4000	19	<0,5	2270	119	760	30160414
Soffite 3 modules LLC900	3000	15	<0,5	1610	107	1060	30170314
Soffite 3 modules LLC900	4000	15	<0,5	1680	112	1060	30170414
Soffite 3 modules LLC1300	3000	27	<0,5	3120	116	1060	30180314
Soffite 3 modules LLC1300	4000	27	<0,5	3250	120	1060	30180414
Soffite 4 modules LLC900	3000	18	<0,5	2260	126	1340	30190314
Soffite 4 modules LLC900	4000	18	<0,5	2350	131	1340	30190414
Soffite 4 modules LLC1300	3000	34	<0,5	4060	119	1340	30200314
Soffite 4 modules LLC1300	4000	34	<0,5	4240	125	1340	30200414
Soffite 5 modules LLC900	3000	27	<0,5	3210	119	1620	30210314
Soffite 5 modules LLC900	4000	27	<0,5	3340	124	1620	30210414
Soffite 5 modules LLC1300	3000	42	<0,5	5120	122	1620	30220314
Soffite 5 modules LLC1300	4000	42	<0,5	5340	127	1620	30220414

SOFFITE LED with Pro detection + standby warning - technical specifications and conditions of use for detection www.securlite.com (NOT0410)							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	<0,5	1280	98	760	30150315
Soffite 2 modules LLC900	4000	13	<0,5	1330	102	760	30150415
Soffite 2 modules LLC1300	3000	19	<0,5	2180	115	760	30160315
Soffite 2 modules LLC1300	4000	19	<0,5	2270	119	760	30160415
Soffite 3 modules LLC900	3000	15	<0,5	1610	107	1060	30170315
Soffite 3 modules LLC900	4000	15	<0,5	1680	112	1060	30170415
Soffite 3 modules LLC1300	3000	27	<0,5	3120	116	1060	30180315
Soffite 3 modules LLC1300	4000	27	<0,5	3250	120	1060	30180415
Soffite 4 modules LLC900	3000	18	<0,5	2260	126	1340	30190315
Soffite 4 modules LLC900	4000	18	<0,5	2350	131	1340	30190415
Soffite 4 modules LLC1300	3000	34	<0,5	4060	119	1340	30200315
Soffite 4 modules LLC1300	4000	34	<0,5	4240	125	1340	30200415
Soffite 5 modules LLC900	3000	27	<0,5	3210	119	1620	30210315
Soffite 5 modules LLC900	4000	27	<0,5	3340	124	1620	30210415
Soffite 5 modules LLC1300	3000	42	<0,5	5120	122	1620	30220315
Soffite 5 modules LLC1300	4000	42	<0,5	5340	127	1620	30220415
SOFFITE LED slave version + extinction warning							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	<0,5	1280	98	760	30150304
Soffite 2 modules LLC900	4000	13	<0,5	1330	102	760	30150404
Soffite 2 modules LLC1300	3000	19	<0,5	2180	115	760	30160304
Soffite 2 modules LLC1300	4000	19	<0,5	2270	119	760	30160404
Soffite 3 modules LLC900	3000	15	<0,5	1610	107	1060	30170304
Soffite 3 modules LLC900	4000	15	<0,5	1680	112	1060	30170404
Soffite 3 modules LLC1300	3000	27	<0,5	3120	116	1060	30180304
Soffite 3 modules LLC1300	4000	27	<0,5	3250	120	1060	30180404
Soffite 4 modules LLC900	3000	18	<0,5	2260	126	1340	30190304
Soffite 4 modules LLC900	4000	18	<0,5	2350	131	1340	30190404
Soffite 4 modules LLC1300	3000	34	<0,5	4060	119	1340	30200304
Soffite 4 modules LLC1300	4000	34	<0,5	4240	125	1340	30200404
Soffite 5 modules LLC900	3000	27	<0,5	3210	119	1620	30210304
Soffite 5 modules LLC900	4000	27	<0,5	3340	124	1620	30210404
Soffite 5 modules LLC1300	3000	42	<0,5	5120	122	1620	30220304
Soffite 5 modules LLC1300	4000	42	<0,5	5340	127	1620	30220404
SOFFITE LED slave version + stand-by warning							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	<0,5	1280	98	760	30150305
Soffite 2 modules LLC900	4000	13	<0,5	1330	102	760	30150405
Soffite 2 modules LLC1300	3000	19	<0,5	2180	115	760	30160305
Soffite 2 modules LLC1300	4000	19	<0,5	2270	119	760	30160405
Soffite 3 modules LLC900	3000	15	<0,5	1610	107	1060	30170305
Soffite 3 modules LLC900	4000	15	<0,5	1680	112	1060	30170405
Soffite 3 modules LLC1300	3000	27	<0,5	3120	116	1060	30180305
Soffite 3 modules LLC1300	4000	27	<0,5	3250	120	1060	30180405
Soffite 4 modules LLC900	3000	18	<0,5	2260	126	1340	30190305
Soffite 4 modules LLC900	4000	18	<0,5	2350	131	1340	30190405
Soffite 4 modules LLC1300	3000	34	<0,5	4060	119	1340	30200305
Soffite 4 modules LLC1300	4000	34	<0,5	4240	125	1340	30200405
Soffite 5 modules LLC900	3000	27	<0,5	3210	119	1620	30210305
Soffite 5 modules LLC900	4000	27	<0,5	3340	124	1620	30210405
Soffite 5 modules LLC1300	3000	42	<0,5	5120	122	1620	30220305
Soffite 5 modules LLC1300	4000	42	<0,5	5340	127	1620	30220405

SOFFITE LED + with Pro detection + radio-control - technical specifications and conditions of use for detection www.securlite.com (NOT0420)							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	0,5	1280	98	760	30150316
Soffite 2 modules LLC900	4000	13	0,5	1330	102	760	30150416
Soffite 2 modules LLC1300	3000	19	0,5	2180	115	760	30160316
Soffite 2 modules LLC1300	4000	19	0,5	2270	119	760	30160416
Soffite 3 modules LLC900	3000	15	0,5	1610	107	1060	30170316
Soffite 3 modules LLC900	4000	15	0,5	1680	112	1060	30170416
Soffite 3 modules LLC1300	3000	27	0,5	3120	116	1060	30180316
Soffite 3 modules LLC1300	4000	27	0,5	3250	120	1060	30180416
Soffite 4 modules LLC900	3000	18	0,5	2260	126	1340	30190316
Soffite 4 modules LLC900	4000	18	0,5	2350	131	1340	30190416
Soffite 4 modules LLC1300	3000	34	0,5	4060	119	1340	30200316
Soffite 4 modules LLC1300	4000	34	0,5	4240	125	1340	30200416
Soffite 5 modules LLC900	3000	27	0,5	3210	119	1620	30210316
Soffite 5 modules LLC900	4000	27	0,5	3340	124	1620	30210416
Soffite 5 modules LLC1300	3000	42	0,5	5120	122	1620	30220316
Soffite 5 modules LLC1300	4000	42	0,5	5340	127	1620	30220416
SOFFITE LED + DALI dimmable + switch dimming + standby warning							
Designation	CCT (K)	Power (W)	Power in stand-by (W)	Luminaire output (lm)	Luminaire efficacy (lm/W)	Lenght (mm)	Code
Soffite 2 modules LLC900	3000	13	<0,5	1280	98	760	30150321
Soffite 2 modules LLC900	4000	13	<0,5	1330	102	760	30150421
Soffite 2 modules LLC1300	3000	19	<0,5	2180	115	760	30160321
Soffite 2 modules LLC1300	4000	19	<0,5	2270	119	760	30160421
Soffite 3 modules LLC900	3000	15	<0,5	1610	107	1060	30170321
Soffite 3 modules LLC900	4000	15	<0,5	1680	112	1060	30170421
Soffite 3 modules LLC1300	3000	27	<0,5	3120	116	1060	30180321
Soffite 3 modules LLC1300	4000	27	<0,5	3250	120	1060	30180421
Soffite 4 modules LLC900	3000	18	<0,5	2260	126	1340	30190321
Soffite 4 modules LLC900	4000	18	<0,5	2350	131	1340	30190421
Soffite 4 modules LLC1300	3000	34	<0,5	4060	119	1340	30200321
Soffite 4 modules LLC1300	4000	34	<0,5	4240	125	1340	30200421
Soffite 5 modules LLC900	3000	27	<0,5	3210	119	1620	30210321
Soffite 5 modules LLC900	4000	27	<0,5	3340	124	1620	30210421
Soffite 5 modules LLC1300	3000	42	<0,5	5120	122	1620	30220321
Soffite 5 modules LLC1300	4000	42	<0,5	5340	127	1620	30220421